

Patent Application Of  
Matthew P. Mitchell  
for  
Improved Foil Structure for Regenerators

**GOVERNMENT RIGHTS**

The invention was made with Government support under contract F29601-99-C-0171 awarded by the United States Air Force. The Government has certain rights in the invention.

**BACKGROUND--FIELD OF INVENTION**

This invention relates to foil for regenerators of regenerative gas cycle machinery.

**BACKGROUND--DESCRIPTION OF PRIOR ART**

Regenerative gas cycle machines are a class of machinery that includes Stirling cycle engines and Stirling cycle, Gifford-McMahon, Vuilleumier, Solvay and pulse tube refrigerators. A regenerator is a critical component of all regenerative gas-cycle machines. The regenerator acts as a thermal sponge. Fluid passing back and forth through the regenerator leaves heat in the regenerator matrix in one direction of flow and picks up that heat as it passes back through the regenerator in the opposite direction.

Stacks of wire-mesh screens, wire felt materials, and beds of packed metal powder have been widely used as regenerators in gas cycle machinery because the materials are primarily used for other purposes, are produced in quantity, and are readily available in the marketplace. However, none of those materials is specifically designed to

09903302-071001

fulfill the special function of a regenerator. Regenerators fabricated from those materials all contain random fluid flow passages in the spaces between wires or grains of powder. The flow passages are of varying width, and a significant portion of the void volume in those regenerator is in spaces in which there is little or no fluid flow and thus little opportunity for heat transfer between the fluid and the regenerator matrix material. One advantage of those prior art materials was that the regenerator permitted lateral flows as well as flows in the overall direction of flow in the regenerator. That permitted imbalances in flow at different points in each cross section of the regenerator to be equalized by natural cross-flows. However, these materials contain no means for dynamically redistributing fluid laterally relative to the overall direction of flow in the regenerator.

Spaced layers of foil have also been used as the matrix material in regenerators in gas cycle machinery. Sheets of foil can be etched to create grooves on the surface of the foil. Foil can also be shaped by crimping or dimpling it, which avoids the loss of material in the etching process, but those techniques have not been sufficiently precise to produce acceptable regenerators. Moreover, solid layers of foil prevent cross-flows necessary to rebalance overall flow distribution over a cross section of the regenerator as fluid moves through it.

Etched foil regenerators used heretofore have partially solved the problem of flow passage width; if the foil is prepared carefully, flow passages are close to the same width throughout the regenerator. Perforations in etched foil have also permitted cross-flows, as in screen, felt and packed powder regenerators. In practice, performance of prior art foil regenerators has generally been disappointing.

Laboratory work with prior art foil regenerators shows that they offer lower pressure drop than felted material, stacked screens or packed powder, the standard regenerator materials. Computer models suggest that prior art foil regenerators should also provide good heat transfer, and, overall, superior performance.

FOOTNOTES: 071001

Disappointing performance of prior art foil regenerators is due in part to inadequate heat transfer between the fluid and the foil. When fluid passes straight through the regenerator from one end to the other, the time that the fluid spends in transit is minimized, limiting the time during which heat transfer can take place. Moreover, boundary layers develop as fluid flows through the regenerator, impeding heat transfer.

Stainless steel can be used in foil regenerators operating down to about 30 Kelvins, but for regenerators to be used in coolers that reach temperatures below about 30 Kelvins, other, more expensive materials with better low-temperature heat capacity are required. Those materials include alloys of rare earth materials. Some of those materials can be formed into foil, but it is not economical to etch that foil to produce perforated regenerator foil because too much of the expensive material would be etched away and thus wasted.

Even with relatively inexpensive materials such as lead and its alloys, etching grooves on the material is not practical because the material is already relatively weak and etching grooves in the material weakens it further, exacerbating problems of handling and assembling it into a regenerator without damaging it.

## SUMMARY OF INVENTION

In accordance with the present invention, a regenerator foil contains grooves on both surfaces, with the grooves intersecting each other to form openings through the foil and with the grooves oriented so as to produce secondary motions in the fluid in one or both sets of grooves. Those secondary motions enhance heat transfer between fluid and foil, thereby improving the performance of the regenerator. Those secondary motions also tend to continually redistribute fluid throughout the whole regenerator in a direction lateral to the overall direction of flow through the regenerator.

Multiple layers of stainless steel foil prepared according to this invention can be used as the heat sink medium for a regenerator with a cold end that operates at

09903302-071001

temperatures above about 35 Kelvin. Layers of stainless steel foil prepared according to this invention can also be interspersed between layers of other materials with greater heat capacity than stainless steel at temperatures below about 35 Kelvin. By employing foil of this invention as spacer material between layers of foil fabricated from alloys of rare earth (Lanthanide) elements, a regenerator effective to temperatures below 10 Kelvin may be fabricated.

## **OBJECTS AND ADVANTAGES**

Several objects and advantages of this invention are:

- (1) To provide high performance foil regenerators for use in gas cycle machines.
- (2) To provide easily-fabricated elements from which foil regenerators may be assembled.
- (3) To provide practical high-performance regenerators for coolers operating at temperatures below 30 Kelvins.
- (4) To provide high performance foil regenerators for use in coaxial pulse tube refrigerators.
- (5) To provide foil regenerators containing materials with high heat capacities at temperatures within a few Kelvins of absolute zero.
- (6) To provide regenerators with high heat transfer rates induced by controlled secondary fluid flows.

Further objects and advantages will become apparent from a consideration of the ensuing description and drawings.

09903302-071001

## Drawing Figures

Fig.1 is a schematic view of a prior art coaxial pulse tube refrigerator.

Fig. 2 is a schematic perspective view of a prior art foil regenerator for a coaxial pulse tube cooler.

Fig. 3 is a schematic perspective view of a prior art foil regenerator, spiral-wrapped on a mandrel.

Fig. 4 is a schematic view of a piece of prior art etched regenerator foil.

Fig. 5 is a schematic representation of flow in the grooves of a piece of regenerator foil of Fig. 4.

Fig. 6A is a schematic perspective view of a piece of regenerator foil of this invention with constant-slant grooves.

Fig. 6B is a schematic view of a piece of regenerator foil of this invention with zigzag-slant grooves.

Fig. 7 illustrates blockage of grooves in a piece of prior art etched regenerator foil.

Fig. 8A illustrates flow in grooves in a piece of regenerator foil of this invention with zigzag spacers.

Fig. 8B illustrates flow in grooves in a piece of regenerator foil of this invention with constant-slant spacers.

Fig. 9A is a schematic perspective view of a piece of spacer foil of this invention with constant-slant grooves.

09903300-071001

Fig. 9B is a schematic view of a piece of spacer foil of this invention with zigzag-slant grooves.

Fig. 9C illustrates the flow patterns in one direction of flow in the spacer foil of Fig. 9B.

Fig 10A is a perspective cutaway view of two layers of solid foil with a layer of spacer foil sandwiched between them.

Fig. 10B illustrates flow in grooves of a piece of regenerator spacer foil of Fig. 10A.

Fig. 11 is a perspective view of a partially unrolled foil regenerator with alternate layers of solid foil and regenerator spacer foil.

#### **Reference Numerals in Drawings**

22 slant-groove spacer foil

26 solid foil

50 compressor

52 piston

54 compression space

56 aftercooler

58 housing

60 regenerator

62 cold heat exchanger

64 pulse tube

66 warm heat exchanger

68 orifice

70 reservoir

80 multiple layers of foil

82 central opening

84 mandrel

09903302-071001

86 unrolled sheet of foil  
 90 strip  
 92 slit  
 94 spacer-strap  
 96 groove, front side  
 98 groove, back side  
 99 unetched spacers  
 100 angled spacer-strap  
 110 hole  
 112 portion depth-etched from front  
 114 portion depth-etched from back  
 116 unetched foil  
 120 heat exchanger fin  
 122 heat exchanger slot  
 124 open groove  
 126 blocked groove  
 130 spacer foil  
 132 solid foil  
 134 lead foil  
 136 lanthanide series alloy  
 138 hot end of regenerator  
 140 cold end of regenerator

**Definitions:** For purposes of this patent, "foil" means sheets of material that are thin relative to their other dimensions. "Surface" as applied to foil means one of the two surfaces of relatively large area, as distinguished from the edges, whose short dimension is approximately the thickness of the foil. "Grooved foil" means foil that has been sculpted, by photoetching or any other process, so that it has grooves on both sides, with the grooves on one side intersecting the grooves on the other side, forming holes in the foil at the places where grooves on opposite sides of the foil intersect. "Continuous" as applied to a groove means a groove at least as long as one complete wrap around a spiral-

09903302.071001

wrapped regenerator, or spanning from edge to edge of a piece of flat foil in a regenerator assembled from multiple separate pieces of foil. "Solid foil" means foil that has not been grooved or perforated. "Overall direction of flow" in a regenerator is the direction of a line drawn from the center of the end of a regenerator where fluid enters to the center of the end of the regenerator where fluid exits, in either direction of flow; individual parcels of fluid moving in the regenerator may follow other paths without altering the overall direction of flow.

### **Description - Figs. 1-5 - Prior Art**

Fig. 1 is a schematic illustration of a prior-art coaxial pulse tube refrigerator. Compressor 50 has a piston 52 that cyclically alters the volume of compression space 54, forcing fluid into and out of other components of the refrigerator including aftercooler 56, regenerator 60, cold heat exchanger 62, pulse tube 64, warm heat exchanger 66, and orifice 68 through which fluid passes into and out of reservoir 70. Although compressor 50 is shown with piston 52, alternate methods of generating cyclically varying pressure, such as a valved compressor, are equivalent.

As fluid flows back and forth through regenerator 60, it leaves heat in the regenerator material as it flows in one direction and picks up heat from the regenerator material as it flows back in the other direction. The material of the regenerator must be porous to permit fluid to flow, and the size and shape of the flow passages determines both the effectiveness of heat transfer between regenerator material and fluid and the amount of pressure drop experienced by the flow. Fig 2 shows detail of a regenerator comprised of multiple layers of foil 80, with a central opening 82, and suited for use in the coaxial pulse tube refrigerator of Fig. 1.

Fig. 3 is a schematic cross section of a prior-art spiral-wrapped foil regenerator according to U.S. Patent 5,429,177. Regenerator foil 61 is wrapped around a mandrel 84 which may be solid or may be a hollow tube that surrounds, or serves as, the pulse tube in the coaxial pulse tube refrigerator of Fig. 1 until the outer diameter of the wrapped

FOOT 20" 20000000

Fig. 4, prior art, illustrates a portion of a piece of regenerator foil of the general prior art type illustrated in Fig. 13 in U.S. Patent 5,429,177. The foil is etched from both sides to create relatively short grooves normal to the overall direction of flow. The grooves are interrupted by spacer-straps 94 of foil that has not been etched completely through; spacer straps 94 hold the piece of foil together. Grooves 96 are entirely on the front side of the foil as drawn. Grooves 96 are arranged in a zigzag pattern relative to the overall direction of flow in the regenerator.

Fig. 6A shows the structure of a portion of a piece of regenerator foil of this invention. The overall direction of flow in the regenerator is between the top and bottom edges of the piece as shown. Strips 90 normal to the overall direction of flow comprise the back side of the piece of foil. Spacers 100 on the front side of the piece of foil are angled relative to the overall direction of flow, and relative to strips 90 on the back side. In practice, the etching process rounds the sharp edges shown schematically in Fig. 6A.

Fig. 6B shows an alternate structure of a portion of a piece of regenerator foil of this invention. The overall direction of flow in the regenerator is between the top and bottom edges of the piece as shown. Strips 90 normal to the overall direction of flow comprise the back side of the piece of foil. Spacer straps 94 on the front side of the piece of foil are again angled relative to the overall direction of flow, and relative to the strips 90 on the back side of the piece of foil, but instead of stretching diagonally across the whole piece of foil, the slant of the spacer straps 94 periodically reverses. The reversal of

direction occurs where spacer straps 94 cross the slits 92 between strips. Grooves 98 on the back side pass under spacer straps 94 which remain unetched on the front side.

Fig. 7 illustrates blockage of grooves in a piece of prior art regenerator foil where a prior art foil regenerator meets heat exchanger comprised of a block of metal fabricated to leave heat exchanger fins 120 on either side of heat exchanger slot 122. Grooves 124 are open to heat exchanger slot 122 but grooves 126 terminate against heat exchanger fins 120.

Fig. 8A illustrates flow patterns in one direction of flow in the grooves in the foil of Fig. 6B. The largest arrows indicate the principal flow, which follows a zigzag path in the grooves, front side 96 of Fig. 6B. The horizontal arrows show uninterrupted induced flows in grooves, back side 98 of Fig. 6B. The curved arrows indicated smaller flows periodically entering and leaving the continuous horizontal flow.

Fig. 8B illustrates flow patterns in one direction of flow in the grooves in the foil of Fig. 6A. The largest arrows indicate the principal flow, which follows a diagonal path in the grooves, front side 96 of Fig. 6A. The horizontal arrows show uninterrupted induced flows in grooves, back side 98, of Fig. 6B. The curved arrows indicated smaller flows periodically entering and leaving the continuous horizontal flow on the back side.

Fig. 9A shows the structure of a portion of a piece of spacer foil of this invention. The overall direction of flow in the regenerator is between the top and bottom edges of the piece as shown. However, the grooves that form grooves, front side 96 and grooves, back side 98, are slanted relative to the overall direction of flow. That is, the grooves on the front side of the foil are angled down to the right and the grooves on the back side are angled down to the left. Where the grooves cross each other, there are holes in the foil. Where spacer straps 100 intersect each other, the full thickness of the original foil remains. The structure can be obtained by photoetching a piece of stainless steel foil in a manner known to the art. The structure is obtained by depth-etching grooves on both sides of the foil while leaving angled spacer straps 100 between grooves.

FOOT 207 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000

Fig. 9B shows the structure of a piece of spacer foil of this invention. The overall direction of flow in the regenerator is between the top and bottom edges of the piece as shown. The foil is etched in a pattern that creates zigzag grooves that cross and recross each other. The structure is obtained by etching a piece of solid foil in some places from one side, in some places from the other side, in some places from both sides (creating a hole) and in some places not at all. Holes 110, portions depth-etched from the front 112, portions depth-etched from the back 114 and portions of unetched foil 116 are arranged to create the flow pattern shown in Fig. 9C.

Fig. 9C shows the main flow pattern in the grooves in the portion of the piece of foil shown in Fig. 9B. The dark arrows show the main flow on the front side of the foil. The lighter arrows show the pattern of flow in the grooves on the back side. Although flow direction on both sides reverses periodically, the flows on front and back sides cross each other repeatedly.

Fig 10A is a perspective cutaway view of two layers of solid foil with a layer of spacer foil sandwiched between them. A piece of slant-groove spacer foil 130 as shown in Fig. 9A is sandwiched between two pieces of solid foil 132.

Fig. 10B illustrates schematically the interaction of flow in intersecting grooves in slant-groove spacer foil 130 when the overall direction of flow in those passages is down and those passages are capped on both sides by solid foil as shown in Fig. 10A.

Fig. 11 shows in perspective a regenerator partially unrolled, with successive layers cut back to show a layer of spacer foil 130 between two layers of solid foil, with a strip of lead foil 138 rolled at the hot end of regenerator 138 and a strip of lanthanide series alloy (alloys containing any of the group of elements consisting of cerium, dysprosium, erbium, europium, gadolinium, holmium, lanthanum, lutetium, neodymium, praseodymium, promethium, samarium, terbium, thulium and ytterbium), rolled at the cold end 140 of the regenerator.

09903302-071001

The basic principle of this invention is that grooves on opposite sides of a sheet of foil are oriented in such a way that when fluid flows in grooves on one side of the sheet, motion is imparted to fluid in grooves on the opposite side of the sheet. The motion imparted to fluid in grooves on the opposite side of the sheet is "induced flow". Induced flow enhances heat transfer, and thereby improves the performance of the regenerator.

An alternate application of this invention is a regenerator comprised of alternate layers of solid foil with good thermal properties and layers of spacer material that need not have comparably good thermal properties. In that embodiment, induced flow is a rotating motion of the flow in grooves on both sides of the spacer material.

## REGENERATOR FOIL

Imperfections in the interface between a regenerator and the heat exchangers at its ends tend to generate significant losses in performance of gas cycle machines. For example, a useful type of cold heat exchanger can be fabricated by cutting slots in a cylindrical copper block. Typically, that type of heat exchanger has wide fins between

slots. Features on the regenerator are typically on a far smaller scale; the ends of the heat exchanger fins tend to contact a relatively large area at the end of a regenerator, blocking flow at the points of contact and channeling flow to a relatively small portion of the cross section of the end of the regenerator, as shown in Fig. 7. The resulting imbalance in flow distribution across the cross section of the regenerator causes thermodynamic losses. The regenerator foil of this invention reduces those losses.

In operation of this invention, flow entering at the edge of the foil through an unblocked groove will be driven through a slant groove 96 in Figs. 6A and 6B until it reaches a groove oriented normal to the overall direction of flow through the regenerator. There, the flow will be forced to either change direction sharply to move into the next slant groove or to change direction less radically to move into a groove oriented normal to the overall direction of flow. The effect will be to drive the flow strongly through the circumferential groove 98 in Fig. 6A and 6B, distributing it around the whole circumference of a layer of regenerator foil in a regenerator such as is shown in Fig. 1.

In foil shown in Fig. 6B, flow must reverse in order to move from a groove normal to the overall direction of flow into the next row of slant grooves. Again, at the end of the next slant grooves, fluid is forced into a circumferential groove from which it eventually emerges, with a change of direction, into yet another row of slant grooves. The flow-reversal process is repeated to ensure even distribution of flow between parallel axial grooves. The pattern shown in Fig. 6B may be repeated across the entire width of a foil in the overall direction of flow or a prior art pattern such as is shown in Fig. 4 or Fig. 7 may be used in the middle of the foil, away from the edges.

In addition to its basic function of redistributing flow, the slant groove pattern enhances regenerator performance in at least two ways. First, by lengthening the flow path of the slant groove relative to the path of an axial groove this invention lengthens the flow distance, increasing heat transfer effectiveness. Second, by driving a flow through the grooves normal to the overall direction of flow, forced convection between fluid and the walls of those grooves is improved, which again enhances heat transfer.

09903302 "071001  
T00T 20E50660

## SPACER FOIL

When a regenerator of this invention is constructed from alternate layers of spacer foil and solid foil, the flow grooves on both sides of the spacer foil layers are capped by the adjacent layers of solid foil as shown in Fig. 10A. The solid foil layers provide the bulk of the heat capacity in the regenerator; the function of the spacer foil is primarily to facilitate heat transfer to and from the layers of solid foil. While the spacer foil contributes some heat capacity, the heat capacity of the regenerator as a whole is provided primarily by the solid foil.

The effect is that each front-side stream tends to push the edges of the intersecting back-side streams in the direction that the front-side stream is going, imparting a rotating motion to the back-side streams. The same is true the other way around; back-side flows tend to induce rotation in the front-side flows. That effect is illustrated in Fig. 10B.

The structure of the spacers is designed to cause fluid to flow diagonally across each side of the foil from edge to edge or, in a cylindrical regenerator, to trace helical paths from one end of the regenerator to the other. The direction of rotation of helical flows on one side of each layer of spacer foil is the opposite of the direction of rotation of on the other side. The angle of the spacers determines the pitch of the helixes, and thus the distance that fluid must flow to move from one end of the regenerator to the other. A smaller angle produces a shorter flow path and less violent interaction where streams on opposite side of the spacer foil cross each other. A larger angle creates more violent interaction. A larger angle also creates a longer flow path and thus a larger opportunity for heat transfer. Both the extent of interaction between the intersecting streams and the length of the flow paths for those streams affect both heat transfer and pressure drop. Optimization of the angle between flow grooves on the front and back sides of the spacer material depends on the particulars of the application, particularly the type of cryocooler and frequency at which it operates. Optimization can be accomplished by techniques known to the art.

09903302 "071001

Etched stainless steel foil is an appropriate spacer material, but other materials could also be formed into an appropriate grid shape to accomplish the intended purpose of guiding flows between the layers of solid foil. Preferred dimensions of materials for a cryocooler regenerator are 75 microns (.003") thick for the solid foil and 50 microns (.002") for maximum thickness of spacer foil (i.e. at the intersections of spacer bars).

The width of the spacers and the flow grooves between them, relative both to each other and to the thickness of the spacer layer, should be such that the main direction of flow in each flow groove is maintained. If the grooves are wide relative to the thickness of the spacer layer, flow will tend to move straight through the regenerator, weaving back and forth from grooves on one side of the spacer layer to grooves on the other side. If, however, the grooves are narrow, flow will tend to follow those grooves, interacting with flow in grooves on the other side of the spacer mainly by rotating. As a first approximation, grooves in the spacer layer should be the minimum width that is possible to be achieved by a photoetching process.

Similarly, the spacers between grooves should be optimized to achieve the desired vortex flow in the grooves while maximizing the heat transfer surface in contact with the fluid. If the spacers are relatively wide, the intersections will be widely spaced, which is desirable in maintaining separate flow in each channel but tends to blank out much of the heat transfer surface of the solid foil. The frequency of the cycle of the gas cycle machine will determine the effective penetration depth of heat moving in and out of the solid foil. At low speeds, in the order of a few Hertz, it may be possible to achieve adequate heat penetration even into the material of the solid foil that is in contact with the spacers. Again, optimization of the spacer bar width can be accomplished by techniques known to the art.

09903302-071001

If different solid foil material is desired at different locations through the regenerator, it may be assembled with narrow strips of several different solid foil materials. The solid foil may thus have thermal properties optimized for the temperature gradient from one end of the regenerator to the other. A single piece of spacer material may be inserted between mixed layers of solid foil comprised of different materials as shown in Fig. 11.

## CONCLUSION, RAMIFICATIONS, AND SCOPE

This invention improves upon prior art foil regenerators by employing patterns that force rather than merely permit secondary flows. As a consequence, although the overall direction of flow in a regenerator of this invention is not altered, the flow paths that individual parcels of fluid follow in passing through the regenerator continually redistribute flows circumferentially in an annular regenerator in which each layer is regenerator foil bearing the same pattern of grooves.

The principle of dynamic generation of secondary flows is also employed in a composite regenerator in which layers of spacer foil with indifferent heat capacity are interleaved with layers of solid foil made from materials with superior heat capacity at the temperatures that those layers experience in operation. Interaction of intersecting streams in grooves on the spacer foil generates a rotating motion in each stream, enhancing heat transfer between the fluid and the solid foil with which it comes in contact.

Although the description above contains many specifics, these should not be construed as limiting the scope of the invention but merely as providing illustrations of some of the presently preferred embodiments of this invention. Thus, the scope of the invention should be determined by the appended claims and their legal equivalents, rather than by the examples given.

00003302-071001